

Cross World Wind
New Series Air Curtains



Cross World Wind
New Series Air Curtains

Cross World Wind
Air Curtains

Artistry, European Quality

The expansion
of reliable and
precision range
of air Curtains

CROSS
Air
Air Curtains



Most Important Silent Features

❖ *154 mm ABS Glass Filled Blower Wheel Suitable for Industrial & Domestic Applications.*

❖ *2 Speed*

❖ *Sleek Design*

❖ *Low Noise*

❖ *Light Weight*

❖ *Aluminium Body, ABS casing*

❖ *Corrosion Resistant*

Human Design

Through extensive research and development cross has come up with a high technology solution to noise control: the result is a strong and even air-flow with minimum noise disturbance.

Maintaining a constant internal environment, a comfortable temperature is ensured whilst the air is kept fresh. Remotely controlled and easy to operate with the surge protection.



Easy to open, convenient design which does not use screws.



The stainless cover is made from high-tech aluminum and ABS of high quality.



With a uniquely designed wind flow baffle, it can produce wind in all directions, working well in various environments.



It can be operated at the touch of a button. It has high and low switch functions.

Fan Wheel

The unique birthplace flows the wind wheel air flue design, uses the high accuracy ABS manufacture: Can the high speed transient equilibrium low noise revolution.



Comfort System

Maintaining a constant internal environment, a comfortable temperature is ensured whilst the air is kept fresh.



Motor

It adopts the technology of electrical machinery. It runs smoothly with powerful air-flow it operates reliably. And runs safely for 5,000 Consecutive hours.



Model	Diameter of wheel (mm)	Dimension (mm)	Frequency (Hz)	Voltage (V~)	Max input Power (W)	Air volume (m3/h)		Air velocity (m/s)(dB)		Noise	Net weight (Kg)
						Hi	Lo				
CF -1506	154	600x260x210	50/60	220-240	250	1598	1220	12-15	< 60	12.5	
CF -1509	154	900x260x210	50/60	220-240	300	1814	1486	12-15	< 62	14.5	
CF -1510	154	1000x260x210	50/60	220-240	320	2020	1722	12-15	< 63	16	
CF -1512	154	1200x260x210	50/60	220-240	365	2732	2277	12-15	< 64	17.5	
CF -1515	154	1500x260x210	50/60	220/240	540	3327	2773	12-15	< 65	21	
CF -1518	154	1800x260x210	50/60	220/240	650	3568	2973	12-15	< 67	24.5	

Technical specification is subject to change without prior notice.

Invisible Door Making life more comfortable inside

